



Selection Guide

10" Industrial TFT Panel Monitor



	AT-IP10	AT-IP10TS	AT-IP10TU
Specification			
Display			
Display Type	10.4" SVGA TFT LCD		
Resolution	800 (H) x 600 (V)		
Pixel Pitch	0.264 (H) x 0.264 (V) (mm)		
Display Color	262k		
Brightness	220 cd/m ²		
Contrast Ratio	400:1		
Viewing Angle	L/R:-60° +60°, U/D:-65° +35°		
Response Time	45 (Tr+Tf) (ms)		
Back Light MTBF	20,000 (hour)		
Construction	Aluminium chassis with VESA 75/ 100mm standard screw holes		
OS Support	MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP		
Menu OSD	Yes		
Control	on Frontbezel		
I/O			
Power Input	External 48WDC 12V power adapter		
Audio input	Line-in		
Video input	15 pin D-SUB, AV input		
Touch Screen			
Type	Five-wire Analog resistive		
Controller	RS-232	USB	
Resolution	continuous		
Light transmission	79%or more		
Power consumption	<5V @100Ma		



Industrial Monitor

10" Industrial TFT Panel Monitor

10"

262K

220 cd/m²



Display	
Display Type	10.4" SVGA TFT LCD
Resolution	800 (H) x 600 (V)
Pixel Pitch	0.264 (H) x 0.264 (V) (mm)
Display Color	262k
Brightness	220 cd/m ²
Contrast Ratio	400:1
Viewing Angle	L/R:-60° +60°, U/D:-65°, +35°
Response Time	45 (Tr+Tf) (ms)
Back Light MTBF	20,000 (hour)
Construction	Aluminium chassis with VESA 75/ 100mm standard screw holes
OS Support	MS DOS, Windows 98/SE, Windows NT4.0, Windows 2000, Windows XP
Menu OSD	Yes
Control	on Frontbezel

Order Information	
AT-IP10	10.4" Industrial TFT Panel Monitor 4:3
AT-IP10TU	10.4" Industrial TFT Panel Monitor, Touch Screen, USB
AT-IP10TS	10.4" Industrial TFT Panel Monitor, Touch Screen, RS232
Option	
AT-IP-EXAV	AV Connector instead serie

I/O	
Power Input	External 48WDC 12V power adapter
Audio input	Line-in
Video input	15 pin D-SUB, AV input (Optional)

Touch Screen	
Type	Five-wire Analog resistive
Controller	RS-232 (AT-IP10TS) USB (AT-IP10TU)
Resolution	continuous
Light transmission	79%or more
Power consumption	<5V @100Ma

Mechanical and Environmental	
Operating temperature	0 °C~ 45°C(32°F~ 113°F)
Storage temperature	-20°C~60°C(-4°F~ 140°F)
Dimensions	314 x 220 x 42.8mm
Gross Weight	3.4 kg

DRAWING

