


# 46" Touch Monitor



## LCD Specification

Viewable Size Image	46"(16:9)
Active Display Area(mm)	1018.08(H) x 572.67(V)
Number of Pixels	1920 x 1080
Contrast Ratio	4000 : 1
Display Color	16.7 million
Brightness(cd/m)	500
Viewing Angle	R/L178° x U/D178°
Recommended Resolution	1920 x 1080 @ 60Hz
Response time	6.5 ms
Life time	50,000/hr
Speaker Output	2 x 2 w internal speaker
Signal Input	1 x VGA, 1 x DVI

## Mechanical

Operating Temp.	0°~50°C
Humidity	20~80% RH
Store Temp.	-20°~55°C
Dimensions(mm)	1115(L)x668(W)x72(D)
Wall Mount(LxW/mm)	600(L) x 200(W)
Color	Black

## Accessories

- DVI Wire x 1
- 3.5" Audio Wire x 1
- Power Core x 1

## Power

Power Input	110V/220V AC
Power Consumption	100 W

## Infrared Touch

- Windows 8/7/Vista /XP, MAC OS X, Linux, Android etc.
- Support panels of flat type for LCD.

Touch Points	2,4,6,10,16,20 touch points. (Options)
Operating Temp.	-20 °C ~ 60 °C.
Operating Hum.	10%~90% RH
Storage Temp.	-40 °C ~ 85 °C.
Touch Activation Force	No pressure required.
Touch Accuracy	± 2mm on more than 95% touch area.
Min Touch Diameter	5 mm.
Response time	First click<16ms, Repeated click<6ms.
Light-proof Capacity	Resisting lights from all angles
Input Method	Fingers, stylus, gloves or any other opaque material medium.
Hohs' hardness rating	7.
Break Resistance	6mm Heat Tempered Glass. Meets UL-1950 Steel Ball Drop Test.
Light Transmission	>92%. (per ASTM D1003)